

**1500**

CANADIAN SPECIFICATIONS

## 2013 Ram 1500 CANADIAN SPECIFICATIONS

All dimensions are in millimetres (inches) unless otherwise noted.

All dimensions are measured at curb weight with standard wheels and tires unless otherwise noted.

NOTE: Information shown is correct at time of publication and is subject to change.

### GENERAL INFORMATION

Vehicle Type	Regular Cab, Quad Cab, and Crew Cab, 2WD, 4WD
Assembly Plant	Regular Cab: Saltillo, Mexico Quad Cab: Warren, Michigan, U.S.A. Crew Cab: Warren, Michigan, U.S.A.
Vehicle Class	Standard Pickup

### BODY/CHASSIS

Layout	2WD — Longitudinal, front engine 4WD — Longitudinal, front engine, transfer case
Construction	2WD — Ladder-type frame, steel cab, double-wall steel pickup box 4WD — Ladder-type frame, steel cab, double-wall steel pickup box

### ENGINE: 3.6-LITRE 24-VALVE DOHC V6

Type and Description	60-degree V-type, liquid-cooled
Displacement	3604 cu. cm (220 cu. in.)
Bore x Stroke	96.0 mm x 83.0 mm (3.78 in. x 3.27 in.)
Valve System	Chain-driven DOHC, 24 valves and hydraulic end-pivot roller rockers
Fuel Injection	Sequential, multi-port, electronic, returnless
Construction	Aluminum deep-skirt block, aluminum alloy heads
Compression Ratio	10.2:1
Power	305 hp at 6,400 rpm
Torque	269 lb.-ft. at 4,175 rpm
Max. Engine Speed	6,400 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane (R+M)/2, E85-compatible for non-fee applications
Oil Capacity	5.7L (6.0 qt.)
Coolant Capacity	13.25L (14.0 qt.)
Emission Controls	Dual three-way catalytic converters, heated oxygen sensors
Estimated EnerGuide Fuel Economy L/100 km (mpg) (City/Hwy)	TBA

**1500**

CANADIAN SPECIFICATIONS

**ENGINE: 4.7-LITRE SOHC 16-VALVE SMPI V8 E85**

Type and Description	90-degree V8, liquid-cooled
Displacement	4701 cu. cm (287 cu. in.)
Bore x Stroke	93.0 mm x 86.5 mm (3.66 in. x 3.40 in.)
Valve System	Chain-driven SOHC, 16 valves
Fuel Injection	Sequential, multi-port, electronic, returnless
Construction	Cast-iron block, aluminum alloy heads
Compression Ratio	9.0:1
Power	310 hp @ 5,650 rpm
Torque	330 lb.-ft. @ 3,950 rpm
Max. Engine Speed	6,000 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane (R+M)/2, E85-compatible
Oil Capacity	5.7L (6.0 qt.)
Coolant Capacity	10.23L (10.8 qt.)
Emission Controls	Three-way catalytic converters, heated oxygen sensors and internal engine features
Estimated EnerGuide Fuel Economy L/100 km (mpg) (City/Hwy)	TBA

**ENGINE: 5.7-LITRE HEMI® 16-VALVE V8**

Type and Description	90-degree V8, liquid-cooled
Displacement	5654 cu. cm (345 cu. in.)
Bore x Stroke	99.5 mm x 90.9 mm (3.92 in. x 3.58 in.)
Valve System	Variable cam timing, pushrod-operated overhead valves, 16 valves, hydraulic lifters with roller followers
Fuel Injection	Sequential, multi-port, electronic, returnless
Construction	Deep-skirt cast-iron block with cross-bolted main bearing caps, aluminum alloy heads with hemispherical combustion chambers
Compression Ratio	10.5:1
Power	395 hp @ 5,600 rpm
Torque	407 lb.-ft. @ 3,950 rpm
Max. Engine Speed	5,800 rpm
Fuel Requirement	Unleaded mid-grade, 89 octane (R+M)/2 — recommended Unleaded regular, 87 octane (R+M)/2 — acceptable
Oil Capacity	6.6L (7.0 qt.)
Coolant Capacity	13.33L (14.0 qt.)
Emission Controls	Three-way catalytic converters, heated oxygen sensors and internal engine features
Estimated EnerGuide Fuel Economy L/100 km (mpg) (City/Hwy) 8-speed automatic	TBA
Estimated EnerGuide Fuel Economy L/100 km (mpg) (City/Hwy) 6-speed automatic	TBA

**1500**

CANADIAN SPECIFICATIONS

**TRANSMISSION: 65RFE AUTOMATIC SIX-SPEED**

Availability	Standard with 4.7-litre V8, available with 5.7-litre V8 equipped trucks
Description	Three planetary gear sets, one overrunning clutch, full electronic control, electronically controlled converter clutch
Gear Ratios	
1st	3.00
2nd	1.67
3rd	1.50
4th	1.00
5th	0.75
6th	0.67
Reverse	3.00
Final Drive and Overall Top Gear Ratios	2.15 with 3.21 axle; 2.38 with 3.55 axle; 2.63 with 3.92 axle; and 2.75 with 4.10 axle
Max Torque	410 lb.-ft.

**TRANSMISSION: ZF 8HP45 AUTOMATIC EIGHT-SPEED WITH ELECTRONIC RANGE SELECT (ERS)**

Availability	Standard with 3.6-litre V6 equipped trucks
Description	Adaptive electronic control, automatic or Electronic Range Select (ERS) manual control. Five clutch-pack design with only two open clutches in any gear. Torque converter lock with turbine torsional damper for low lock-up speeds in 1st through 8th gear
Gear Ratios	
1st	4.71
2nd	3.14
3rd	2.10
4th	1.67
5th	1.29
6th	1.00
7th	0.84
8th	0.67
Reverse	3.30
Final Drive and Overall Top Gear Ratios	2.15 with 3.21 axle; 2.38 with 3.55 axle
Max Torque	332 lb.-ft.

**TRANSMISSION: ZF 8HP70 AUTOMATIC EIGHT-SPEED WITH ELECTRONIC RANGE SELECT (ERS)**

Availability	Available with select 5.7-litre V8 equipped trucks (late availability)
Description	Adaptive electronic control, automatic or ERS manual control. Five clutch-pack design with only two open clutches in any gear. Torque converter lock with turbine torsional damper for low lock-up speeds in 1st through 8th gear

**1500**

CANADIAN SPECIFICATIONS

<b>Gear Ratios</b>	
1st	4.71
2nd	3.14
3rd	2.10
4th	1.67
5th	1.29
6th	1.00
7th	0.84
8th	0.67
Reverse	3.30
Final Drive and Overall Top Gear Ratios	2.15 with 3.21 axle; 2.38 with 3.55 axle; 2.63 with 3.92 axle
Max Torque	516 lb.-ft.

**TRANSFER CASE: BW 44-45 PART-TIME**

Availability	3.6-litre V6 4x4, 4.7-litre V8 4x4 and 5.7-litre V8 4x4
Shift Mechanism	Electric
Available Speeds	2-speed
Operating Modes	2WD High; 4WD High, Locked; Neutral; 4WD Low, Locked
Low-range Ratio	2.64
Centre Differential Type	None

**TRANSFER CASE: BW 44-44 ON-DEMAND**

Availability	5.7-litre V8 4x4
Shift Mechanism	Electric
Available Speeds	2-speed
Operating Modes	2WD High; 4WD Auto; 4WD High, Locked; Neutral; 4WD Low, Locked
Low-range Ratio	2.64
Centre Differential Type	None

**AXLES**

Front	ZF 215MM
Rear	C235MM (available limited slip)
Available Ratios	3.21, 3.55, 3.92, 4.10

**ELECTRICAL SYSTEM**

Architecture	Powernet
Alternator	160-amp, 180-amp, 220-amp (Stop-start only)
Battery	Group 65, low-maintenance 730 CCA (Stop-start features 800 CCA Absorbed Glass Mat)

**1500**

CANADIAN SPECIFICATIONS

**SUSPENSION**

Front	Upper and lower "A" arms, coil springs, twin-tube shock absorbers, stabilizer bar. Optional air suspension replaces twin-tube shock absorbers and coil springs
Rear	Five-link with track bar, coil springs, stabilizer bar, twin-tube shock absorbers, solid axle. Optional air suspension replaces twin-tube shock absorbers and coil springs

**STEERING**

Power-assist	Electric power steering
--------------	-------------------------

<b>Regular Cab</b>	<b>2WD</b>	<b>2WD</b>	<b>4WD</b>	<b>4WD</b>
Box Length	Short box	Long Box	Short Box	Long Box
Wheelbase (nominal)	3061 (120.5)	3569.2 (140.5)	3569.2 (140.5)	3569.2 (140.5)
Overall Steering Ratio	19.1:1	17.9:1	19.1:1	17.9:1
Steering Wheel Turns (lock-to-lock)	3.5	3.3	3.5	3.3
Turning Diameter – 17-in. Tire –m (ft.) <sup>(a)</sup>	12.0 (39.5)	13.7 (45.1)	12.1 (39.8)	13.8 (45.4)
Turning Diameter – 20-in. Tire - m (ft.) <sup>(a)</sup>	12.0 (39.3)	13.7 (44.9)	12.1 (39.8)	13.9 (45.5)
Turning Diameter – 17-in. Outdoorsman Tire – m (ft.) <sup>(a)</sup>	N/A	N/A	12.0 (39.4)	13.7 (45.0)

<b>Quad Cab</b>	<b>2WD</b>	<b>4WD</b>
Box Length	Long Box	Long Box
Wheelbase (nominal)	3569.2 (140.5)	3569.2 (140.5)
Overall Steering Ratio	17.9:1	17.9:1
Steering Wheel Turns (lock-to-lock)	3.3	3.3
Turning Diameter – 17-in. Tire –m (ft.) <sup>(a)</sup>	13.7 (45.1)	13.8 (45.4)
Turning Diameter – 20-in. Tire - m (ft.) <sup>(a)</sup>	13.7 (44.9)	13.9 (45.5)
Turning Diameter – 17-in. Outdoorsman Tire – m (ft.) <sup>(a)</sup>	13.7 (44.8)	13.7 (45.0)

<b>Crew Cab</b>	<b>2WD</b>	<b>2WD</b>	<b>4WD</b>	<b>4WD</b>
Box Length	Short box	Long Box <sup>(1)</sup>	Short Box	Long Box <sup>(1)</sup>
Wheelbase (nominal)	3061 (140.5)	3569.2 (149.5)	3569.2 (140.5)	3569.2 (149.5)
Overall Steering Ratio	19.1:1	17.9:1	19.1:1	17.9:1
Steering Wheel Turns (lock-to-lock)	3.5	3.3	3.5	3.3
Turning Diameter – 17-in. Tire –m (ft.) <sup>(a)</sup>	12.0 (39.5)	13.7 (45.1)	12.1 (39.8)	13.8 (45.4)
Turning Diameter – 20-in. Tire - m (ft.) <sup>(a)</sup>	12.0 (39.3)	13.7 (44.9)	12.1 (39.8)	13.9 (45.5)
Turning Diameter – 17-in. Outdoorsman Tire – m (ft.) <sup>(a)</sup>	N/A	N/A	12.0 (39.4)	13.7 (45.0)

(1) Late Availability

**1500**

CANADIAN SPECIFICATIONS

**CHASSIS**

Layout	Longitudinal, front engine (optional transfer case)
Construction	Ladder-type frame, steel cab, double-wall steel pickup box

**BRAKES**

Front	Size and Type 13.2 in. x 1.1 in. (336 mm x 28 mm) vented disc with 2.13 in. (54 mm) two-piston pin-slider caliper and ABS Swept Area 292 sq. in. (1884 sq. cm)
Rear	Size and Type 13.8 in. x 0.87 in. (352 mm x 22 mm) disc with 2.13 in. (54 mm) single-piston pin-slider caliper and ABS Swept Area 274 sq. in. (1768 sq. cm)
Power-assist	Dual-rate, tandem diaphragm vacuum

**DIMENSIONS AND CAPACITIES****Regular Cab Pickup**

<i>Model – Tire Size</i>	<i>2WD –265/70R17</i>		<i>4WD –265/70R17</i>	
<b>Box Length</b>	<i>6ft. 4in.</i>	<i>8ft.</i>	<i>6ft. 4in.</i>	<i>8ft.</i>
Wheelbase (nominal)	3061.2 (120.5)	3569.2 (140.5)	3062.5 (120.5)	3570.2 (140.5)
Track, Front	1728.2 (68.0)	1728.2 (68.0)	1732.3 (68.2)	1732.3 (68.2)
Track, Rear	1714.7 (67.5)	1714.7 (67.5)	1714.7 (67.5)	1714.7 (67.5)
Overall Length	5308.5 (209.0)	5866.5 (231.0)	5308.5 (209.0)	5866.5 (231.0)
Overall Width	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)
Overall Height	1894.2 (74.6)	1889.2 (74.4)	1910.4 (75.2)	1906.2 (75.0)
<b>Ground Clearance</b>				
Front Axle	229.3 (9.0)	229.3 (9.0)	232.6 (9.2)	232.7 (9.2)
Rear Axle	221.2 (8.7)	221.5 (8.7)	219.2 (8.6)	219.5 (8.6)
Open Tailgate to Ground	883.4 (34.8)	878.3 (34.6)	889.6 (35.0)	885.3 (34.9)
Pickup Body Height	511.1 (20.1)	513.0 (20.2)	511.1 (20.1)	513.0 (20.2)
Approach Angle (degrees)	15.6	15.7	17.7	17.8
Departure Angle (degrees)	25.2	24.1	25.6	24.4
Ramp Breakover Angle (degrees)	21.5	19.2	22.9	20.5
Fuel-Tank Capacity	98-litre (Standard)	121-litre (Standard)	98-litre (Standard)	121-litre (Standard)

**Quad Cab 6-ft. 4-in. Box Pickup**

<i>Model – Tire Size</i>	<i>2WD –265/70R17</i>	<i>4WD –265/70R17</i>
Wheelbase (nominal)	3569.2 (140.5)	3570.2 (140.5)
Track, Front	1728.2 (68.0)	1732.3 (68.2)

**1500**

CANADIAN SPECIFICATIONS

Track, Rear	1714.7 (67.5)	1714.7 (67.5)
Overall Length	5816.5 (229.0)	5816.5 (229.0)
Overall Width	2017.4 (79.4)	2017.4 (79.4)
Overall Height	1960.2 (77.2)	1974.8 (77.7)
<b>Ground Clearance</b>		
Front Axle	229.2 (9.0)	232.7 (9.2)
Rear Axle	221.5 (8.7)	219.5 (8.6)
Open tailgate to ground	878.3 (34.6)	885.3 (34.9)
Pickup Body Height	511.1 (20.1)	511.1 (20.1)
Approach Angle (degrees)	15.7	17.8
Departure Angle (degrees)	25.1	25.4
Ramp Breakover Angle (degrees)	19.2	20.5
Fuel-Tank Capacity	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)

**Quad Cab 6ft. 4in. Box Pickup – Outdoorsman**

<b>Model – Tire Size</b>	<b>2WD –275/60R20</b>	<b>4WD –275/60R20</b>
Wheelbase (nominal)	3569.4 (140.5)	3573.5 (140.7)
Track, Front	1742.2 (68.6)	1743.2 (68.6)
Track, Rear	1727.4 (68.0)	1727.4 (68.0)
Overall Length	5816.5 (229.0)	5816.5 (229.0)
Overall Width	2017.4 (79.4)	2017.4 (79.4)
Overall Height	1979.4 (77.9)	2001.6 (78.8)
<b>Ground Clearance</b>		
Front Axle	244.8 (9.6)	248.6 (9.8)
Rear Axle	237.0 (9.3)	233.2 (9.2)
Open tailgate to ground	887.7	903.5
Pickup Body Height	511.1 (20.1)	511.1 (20.1)
Approach Angle (degrees)	21.3	23.9
Departure Angle, (degrees)	21.4	22.1
Ramp Breakover Angle (degrees)	20.9	18.8
Ground Clearance without Skid Plate	261.5 (10.3)	NA
Ground Clearance with Skid Plate	NA	252.2 (9.9)
Fuel-Tank Capacity	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)



**1500**

CANADIAN SPECIFICATIONS

**Quad Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4**

<i>Tire Size</i>	<i>265/70R17</i>			
<b>Suspension Mode</b>	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road 1</i>	<i>Off Road 2</i>
Wheelbase (nominal)	3569.4 (140.5)	3569.4 (140.5)	3569.4 (140.5)	3569.4 (140.5)
Track, Front	1728.2 (68.0)	1728.2 (68.0)	1728.2 (68.0)	1728.2 (68.0)
Track, Rear	1714.7 (67.5)	1714.7 (67.5)	1714.7 (67.5)	1714.7 (67.5)
Overall Length	5816.5 (229.0)	5816.5 (229.0)	5816.5 (229.0)	5816.5 (229.0)
Overall Width	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)
Overall Height	1909.0 (75.2)	1962.0 (77.2)	1986.6 (78.2)	2013.0 (79.2)
<b>Ground Clearance</b>				
Front Axle	232.3 (9.1)	232.3 (9.1)	232.3 (9.1)	232.3 (9.1)
Rear Axle	220.0 (8.7)	220.0 (8.7)	220.0 (8.7)	220.0 (8.7)
Open Tailgate to Ground	832.8 (32.8)	871.2 (34.3)	889.6 (35.0)	922.2 (36.3)
Pickup Body Height	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)
Approach Angle (degrees)	13.8	18.3	20.9	22.5
Departure Angle (degrees)	23.0	24.8	25.6	27.1
Ramp Breakover Angle (degrees)	15.9	19.4	21.4	23.0
Ground Clearance without Skid Plate	171.0 (6.7)	223.5 (8.8)	254 (10.0)	274.3 (10.8)
Ground Clearance with Skid Plate	153.1 (6.0)	205.7 (8.1)	236.2 (9.3)	256.5 (10.1)
Fuel-Tank Capacity	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)

**Quad Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4**

<i>Tire Size</i>	<i>275/60R20</i>			
<b>Suspension Mode</b>	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road 1</i>	<i>Off Road 2</i>
Wheelbase (nominal)	3569.4 (140.5)	3569.4 (140.5)	3569.4 (140.5)	3569.4 (140.5)
Track, Front	1742.2 (68.6)	1742.2 (68.6)	1742.2 (68.6)	1742.2 (68.6)
Track, Rear	1727.4 (68.0)	1727.4 (68.0)	1727.4 (68.0)	1727.4 (68.0)
Overall Length	5816.5 (229.0)	5816.5 (229.0)	5816.5 (229.0)	5816.5 (229.0)
Overall Width	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)
Overall Height	1924.4 (75.8)	1977.4 (77.8)	2002.0 (78.8)	2028.4 (79.9)
<b>Ground Clearance</b>				
Front Axle	248.5 (9.8)	248.5 (9.8)	248.5 (9.8)	248.5 (9.8)
Rear Axle	235.0 (9.3)	235.0 (9.3)	235.0 (9.3)	235.0 (9.3)
Open Tailgate to Ground	847.2 (33.4)	885.7 (34.9)	904.1 (35.6)	936.7 (36.9)
Pickup Body Height	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)
Approach Angle (degrees)	15.2	19.8	22.4	23.9
Departure Angle (degrees)	23.7	25.5	26.4	27.8





# 1500

## CANADIAN SPECIFICATIONS

Ramp Breakover Angle (degrees)	17.1	20.6	22.5	24.2
Ground Clearance without Skid Plate	187.2 (7.4)	239.8 (9.4)	269.5 (10.6)	290.8 (11.4)
Ground Clearance with Skid Plate	169.3 (6.7)	222.8 (8.8)	252.8 (9.9)	273.7 (10.8)
Fuel-Tank Capacity	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)

### Quad Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman

#### Tire Size

**265/70R17**

Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	3569.4 (140.5)	3569.4 (140.5)	3569.4 (140.5)	3569.4 (140.5)
Track, Front	1728.2 (68.0)	1728.2 (68.0)	1728.2 (68.0)	1728.2 (68.0)
Track, Rear	1714.7 (67.5)	1714.7 (67.5)	1714.7 (67.5)	1714.7 (67.5)
Overall Length	5816.5 (229.0)	5816.5 (229.0)	5816.5 (229.0)	5816.5 (229.0)
Overall Width	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)
Overall Height	1909.0 (75.2)	1962.0 (77.2)	1986.6 (78.2)	2013.0 (79.2)
<b>Ground Clearance</b>				
Front Axle	232.3 (9.1)	232.3 (9.1)	232.3 (9.1)	232.3 (9.1)
Rear Axle	220.0 (8.7)	220.0 (8.7)	220.0 (8.7)	220.0 (8.7)
Open Tailgate to Ground	832.8 (32.8)	871.2 (34.3)	889.6 (35.0)	922.2 (36.3)
Pickup Body Height	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)
Approach Angle (degrees)	15.2	19.7	21.8	22.9
Departure Angle (degrees)	18.7	20.6	21.4	22.9
Ramp Breakover Angle without Skid Plate	15.9	19.4	21.4	23.0
Ramp Breakover Angle, with Skid Plate	12.7	15.9	17.6	19.2
Ground Clearance without Skid Plate	171.0 (6.7)	223.5 (8.8)	254 (10.0)	274.3 (10.8)
Ground Clearance with Skid Plate	153.1 (6.0)	205.7 (8.1)	236.2 (9.3)	256.5 (10.1)
Fuel-Tank Capacity	98-litre (Standard) 121litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)

### Quad Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman

#### Tire Size

**275/60R20**

Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	3569.4 (140.5)	3569.4 (140.5)	3569.4 (140.5)	3569.4 (140.5)
Track, Front	1742.2 (68.6)	1742.2 (68.6)	1742.2 (68.6)	1742.2 (68.6)
Track, Rear	1727.4 (68.0)	1727.4 (68.0)	1727.4 (68.0)	1727.4 (68.0)



# 1500

## CANADIAN SPECIFICATIONS

Overall Length	5816.5 (229.0)	5816.5 (229.0)	5816.5 (229.0)	5816.5 (229.0)
Overall Width	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)
Overall Height	1924.4 (75.8)	1977.4 (77.8)	2002.0 (78.8)	2028.4 (79.9)
<b>Ground Clearance</b>				
Front Axle	248.5 (9.8)	248.5 (9.8)	248.5 (9.8)	248.5 (9.8)
Rear Axle	235.0 (9.3)	235.0 (9.3)	235.0 (9.3)	235.0 (9.3)
Open Tailgate to Ground	847.2 (33.4)	885.7 (34.9)	904.1 (35.6)	936.7 (36.9)
Pickup Body Height	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)
Approach Angle (degrees)	16.6	20.9	22.9	24.0
Departure Angle (degrees)	19.4	21.3	22.2	23.6
Ramp Breakover Angle without Skid Plate	17.1	20.6	22.5	24.2
Ramp Breakover Angle with Skid Plate	13.8	17.0	18.7	20.3
Ground Clearance without Skid Plate	187.2 (7.4)	239.8 (9.4)	269.5 (10.6)	290.8 (11.4)
Ground Clearance with Skid Plate	169.3 (6.7)	222.8 (8.8)	252.8 (9.9)	273.7 (10.8)
Fuel-Tank Capacity	98-litre (Standard) 121-litre (Optional)	(98-litre) (Standard) 121-litre (Optional)	98-litre (Standard) (121-litre) (Optional)	98-litre (Standard) 121-litre (Optional)

### Crew Cab Pickup

<b>Model – Tire Size</b>	<b>2WD – 265/70R17</b>		<b>4WD – 265/70R17</b>	
<b>Box Length</b>	<b>5ft. 7in.</b>	<b>6ft. 4in.</b>	<b>5ft. 7in.</b>	<b>6ft. 4in.</b>
Wheelbase (nominal)	3569.2 (140.5)	3795.3 (149.4)	3570.2 (140.5)	3795.2 (149.4)
Track, Front	1728.2 (68.0)	1728.2 (68.0)	1732.3 (68.2)	1732.3 (68.2)
Track, Rear	1714.7 (67.5)	1714.7 (67.5)	1714.7 (67.5)	1714.7 (67.5)
Overall Length	5816.5 (229.0)	6042.6 (237.9)	5816.5 (229.0)	6042.6 (237.9)
Overall Width	2017.4 (79.4)	2016.6 (79.4)	2017.4 (79.4)	2016.6 (79.4)
Overall Height	1953.8 (76.9)	1950.6 (76.8)	1967.9 (77.5)	1965.1 (77.4)
<b>Ground Clearance</b>				
Front Axle	229.2 (9.0)	231.1 (9.1)	232.7 (9.2)	235.2 (9.2)
Rear Axle	221.5 (8.7)	220.5 (8.7)	219.5 (8.6)	218.3 (8.6)
Open Tailgate to Ground	878.3 (34.6)	874.0 (34.4)	885.3 (34.9)	880.8 (34.7)
Pickup Body Height	508.6 (20.0)	511.1 (20.1)	508.6 (20.0)	511.1 (20.1)
Approach Angle (degrees)	15.7	16.0	17.8	18.0
Departure Angle (degrees)	25.1	24.9	24.7	25.2
Ramp Breakover Angle (degrees)	19.2	18.5	20.5	19.7
Fuel-Tank Capacity	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) (121-litre) (Optional)	98-litre (Standard) 121-litre (Optional)



**1500**

CANADIAN SPECIFICATIONS

**Crew Cab Pickup - Outdoorsman**

<b>Model – Tire Size</b>	<b>2WD –275/60R20</b>		<b>4WD –275/60R20</b>	
<b>Box Length</b>	<b>5ft. 7in.</b>	<b>6ft. 4in.</b>	<b>5ft. 7in.</b>	<b>6ft. 4in.</b>
Wheelbase (nominal)	3569.4 (140.5)	3795.8 (149.4)	3573.5 (140.7)	3799.6 (149.6)
Track, Front	1742.2 (68.6)	1742.2 (68.6)	1742.2 (68.6)	1742.2 (68.6)
Track, Rear	1727.4 (68.0)	1727.4 (68.0)	1727.4 (68.0)	1727.4 (68.0)
Overall Length	5816.5 (229.0)	6042.6 (237.9)	5816.5 (229.0)	6042.6 (237.9)
Overall Width	2017.4 (79.4)	2016.6 (79.4)	2017.4 (79.4)	2016.6 (79.4)
Overall Height	1972.3 (77.6)	1968.1 (77.5)	1994.1 (78.5)	1991.7 (78.4)
<b>Ground Clearance</b>				
Front Axle	244.8 (9.6)	243.6 (9.6)	248.6 (9.8)	248.0 (9.8)
Rear Axle	237.0 (9.3)	235.0 (9.3)	233.2 (9.2)	233.1 (9.2)
Open Tailgate to Ground	887.7 (34.9)	883.9 (34.8)	903.5 (35.6)	902.3 (35.5)
Pickup Body Height	508.6 (20.0)	511.1 (20.1)	508.6 (20.0)	511.1 (20.1)
Approach Angle (degrees)	21.3	21.0	23.9	22.9
Departure Angle (degrees)	21.4	21.2	22.1	22.1
Ramp Breakover Angle (degrees)	20.9	19.9	18.8	17.6
Ground Clearance without Skid Plate	261.5 (10.3)	261.0 (10.3)	NA	NA
Ground Clearance with Skid Plate	NA	NA	252.2 (9.9)	251.6 (9.9)
Fuel-Tank Capacity	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)

**Crew Cab 5ft. 7in. Box Pickup - Air Suspension 4x2 and 4x4**

<b>Tire Size</b>	<b>265/70R17</b>			
<b>Suspension Mode</b>	<b>Entry / Exit</b>	<b>Normal Ride Height</b>	<b>Off Road 1</b>	<b>Off Road 2</b>
Wheelbase (nominal)	3569.4 (140.5)	3569.4 (140.5)	3569.4 (140.5)	3569.4 (140.5)
Track, Front	1728.2 (68.0)	1728.2 (68.0)	1728.2 (68.0)	1728.2 (68.0)
Track, Rear	1714.7 (67.5)	1714.7 (67.5)	1714.7 (67.5)	1714.7 (67.5)
Overall Length	5816.5 (229.0)	5816.5 (229.0)	5816.5 (229.0)	5816.5 (229.0)
Overall Width	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)
Overall Height	1902.1 (74.9)	1955.1 (77.0)	1979.2 (77.9)	2006.1 (79.0)
<b>Ground Clearance</b>				
Front Axle	232.3 (9.1)	232.3 (9.1)	232.3 (9.1)	232.3 (9.1)
Rear Axle	220.0 (8.7)	220.0 (8.7)	220.0 (8.7)	220.0 (8.7)
Open Tailgate to Ground	832.8 (32.8)	871.2 (34.3)	889.6 (35.0)	922.2 (36.3)
Pickup Body Height	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)
Approach Angle (degrees)	13.8	18.3	20.9	22.5
Departure Angle (degrees)	23.0	24.8	25.6	27.1



**1500**

CANADIAN SPECIFICATIONS

Ramp Breakover Angle (degrees)	15.9	19.4	21.4	23.0
Ground Clearance without Skid Plate	171.0 (6.7)	223.5 (8.8)	254 (10.0)	274.3 (10.8)
Ground Clearance with Skid Plate	153.1 (6.0)	205.7 (8.1)	236.2 (9.3)	256.5 (10.1)
Fuel-Tank Capacity	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (32-gal.) (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)

**Crew Cab 5ft. 7in. Box Pickup - Air Suspension 4x2 and 4x4**

**Tire Size**

**275/60R20**

Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	3569.4 (140.5)	3569.4 (140.5)	3569.4 (140.5)	3569.4 (140.5)
Track, Front	1742.2 (68.6)	1742.2 (68.6)	1742.2 (68.6)	1742.2 (68.6)
Track, Rear	1727.4 (68.0)	1727.4 (68.0)	1727.4 (68.0)	1727.4 (68.0)
Overall Length	5816.5 (229.0)	5816.5 (229.0)	5816.5 (229.0)	5816.5 (229.0)
Overall Width	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)
Overall Height	1917.4 (75.5)	1970.4 (77.6)	1994.5 (78.5)	2021.4 (79.6)

**Ground Clearance**

Front Axle	248.5 (9.8)	248.5 (9.8)	248.5 (9.8)	248.5 (9.8)
Rear Axle	235.0 (9.3)	235.0 (9.3)	235.0 (9.3)	235.0 (9.3)
Open Tailgate to Ground	847.2 (33.4)	885.7 (34.9)	904.1 (35.6)	936.7 (36.9)
Pickup Body Height	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)
Approach Angle (degrees)	15.2	19.8	22.4	23.9
Departure Angle (degrees)	23.7	25.5	26.4	27.8
Ramp Breakover Angle (degrees)	17.1	20.6	22.5	24.2
Ground Clearance without Skid Plate	187.2 (7.4)	239.8 (9.4)	269.5 (10.6)	290.8 (11.4)
Ground Clearance with Skid Plate	169.3 (6.7)	222.8 (8.8)	252.8 (9.9)	273.7 (10.8)
Fuel-Tank Capacity	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)

**Crew Cab 5ft. 7in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman**

**Tire Size**

**265/70R17**

Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	3569.4 (140.5)	3569.4 (140.5)	3569.4 (140.5)	3569.4 (140.5)
Track, Front	1728.2 (68.0)	1728.2 (68.0)	1728.2 (68.0)	1728.2 (68.0)
Track, Rear	1714.7 (67.5)	1714.7 (67.5)	1714.7 (67.5)	1714.7 (67.5)
Overall Length	5816.5 (229.0)	5816.5 (229.0)	5816.5 (229.0)	5816.5 (229.0)
Overall Width	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)



**1500**

CANADIAN SPECIFICATIONS

Overall Height	1902.1 (74.9)	1955.1 (77.0)	1979.2 (77.9)	2006.1 (79.0)
<b>Ground Clearance</b>				
Front Axle	232.3 (9.1)	232.3 (9.1)	232.3 (9.1)	232.3 (9.1)
Rear Axle	220.0 (8.7)	220.0 (8.7)	220.0 (8.7)	220.0 (8.7)
Open Tailgate to Ground	832.8 (32.8)	871.2 (34.3)	889.6 (35.0)	922.2 (36.3)
Pickup Body Height	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)
Approach Angle (degrees)	15.2	19.7	21.8	22.9
Departure Angle (degrees)	18.7	20.6	21.4	22.9
Ramp Breakover Angle without Skid Plate	15.9	19.4	21.4	23.0
Ramp Breakover Angle with Skid Plate	12.7	15.9	17.6	19.2
Ground Clearance without Skid Plate	171.0 (6.7)	223.5 (8.8)	254 (10.0)	274.3 (10.8)
Ground Clearance with Skid Plate	153.1 (6.0)	205.7 (8.1)	236.2 (9.3)	256.5 (10.1)
Fuel-Tank Capacity	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)

**Crew Cab 5ft. 7in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman**

**Tire Size**

**275/60R20**

<b>Suspension Mode</b>	<b>Entry / Exit</b>	<b>Normal Ride Height</b>	<b>Off Road 1</b>	<b>Off Road 2</b>
Wheelbase (nominal)	3569.4 (140.5)	3569.4 (140.5)	3569.4 (140.5)	3569.4 (140.5)
Track, Front	1742.2 (68.6)	1742.2 (68.6)	1742.2 (68.6)	1742.2 (68.6)
Track, Rear	1727.4 (68.0)	1727.4 (68.0)	1727.4 (68.0)	1727.4 (68.0)
Overall Length	5816.5 (229.0)	5816.5 (229.0)	5816.5 (229.0)	5816.5 (229.0)
Overall Width	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)
Overall Height	1917.4 (75.5)	1970.4 (77.6)	1994.5 (78.5)	2021.4 (79.6)
<b>Ground Clearance</b>				
Front Axle	248.5 (9.8)	248.5 (9.8)	248.5 (9.8)	248.5 (9.8)
Rear Axle	235.0 (9.3)	235.0 (9.3)	235.0 (9.3)	235.0 (9.3)
Open Tailgate to Ground	847.2 (33.4)	885.7 (34.9)	904.1 (35.6)	936.7 (36.9)
Pickup Body Height	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)	508.6 (20.0)
Approach Angle (degrees)	16.6	20.9	22.9	24.0
Departure Angle (degrees)	19.4	21.3	22.2	23.6
Ramp Breakover Angle without Skid Plate	17.1	20.6	22.5	24.2
Ramp Breakover Angle with Skid Plate	13.8	17.0	18.7	20.3
Ground Clearance without Skid Plate	187.2 (7.4)	239.8 (9.4)	269.5 (10.6)	290.8 (11.4)
Ground Clearance with Skid Plate	169.3 (6.7)	222.8 (8.8)	252.8 (9.9)	273.7 (10.8)
Fuel-Tank Capacity	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)

**1500**

CANADIAN SPECIFICATIONS

**Crew Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4**

<b>Tire Size</b>	<b>265/70R17</b>			
<b>Suspension Mode</b>	<b>Entry / Exit</b>	<b>Normal Ride Height</b>	<b>Off Road 1</b>	<b>Off Road 2</b>
Wheelbase (nominal)	3798.0 (149.50)	3798.0 (149.50)	3798.0 (149.50)	3798.0 (149.50)
Track, Front	1728.2 (68.0)	1728.2 (68.0)	1728.2 (68.0)	1728.2 (68.0)
Track, Rear	1714.7 (67.5)	1714.7 (67.5)	1714.7 (67.5)	1714.7 (67.5)
Overall Length	6042.6 (237.9)	6042.6 (237.9)	6042.6 (237.9)	6042.6 (237.9)
Overall Width	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)
Overall Height	1897.7 (74.7)	1950.7 (76.8)	1975.2 (77.8)	2001.7 (78.8)
<b>Ground Clearance</b>				
Front Axle	231.6 (9.1)	231.6 (9.1)	231.6 (9.1)	231.6 (9.1)
Rear Axle	217.7 (8.6)	217.7 (8.6)	217.7 (8.6)	217.7 (8.6)
Open Tailgate to Ground	827.9 (32.6)	866.6 (34.1)	885.2 (34.8)	917.6 (36.1)
Pickup Body Height	511.1 (20.1)	511.1 (20.1)	511.1 (20.1)	511.1 (20.1)
Approach Angle (degrees)	13.8	18.3	20.9	22.5
Departure Angle (degrees)	22.8	24.6	25.5	26.9
Ramp Breakover Angle (degrees)	15.3	18.7	20.5	22.2
Ground Clearance without Skid Plate	170.0 (6.7)	222.7 (8.8)	252.4 (9.9)	273.7 (10.8)
Ground Clearance with Skid Plate	152.3 (6.0)	205.4 (8.1)	235.4 (9.3)	256.4 (10.1)
Fuel-Tank Capacity	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)

**Crew Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4**

<b>Tire Size</b>	<b>275/60R20</b>			
<b>Suspension Mode</b>	<b>Entry / Exit</b>	<b>Normal Ride Height</b>	<b>Off Road 1</b>	<b>Off Road 2</b>
Wheelbase (nominal)	3798.0 (149.5)	3798.0 (149.5)	3798.0 (149.5)	3798.0 (149.5)
Track, Front	1742.2 (68.6)	1742.2 (68.6)	1742.2 (68.6)	1742.2 (68.6)
Track, Rear	1727.4 (68.0)	1727.4 (68.0)	1727.4 (68.0)	1727.4 (68.0)
Overall Length	6042.6 (237.9)	6042.6 (237.9)	6042.6 (237.9)	6042.6 (237.9)
Overall Width	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)
Overall Height	1914.5 (75.4)	1967.5 (77.5)	1991.9 (78.4)	2018.5 (79.5)
<b>Ground Clearance</b>				
Front Axle	247.9 (9.8)	247.9 (9.8)	247.9 (9.8)	247.9 (9.8)
Rear Axle	234.7 (9.2)	234.7 (9.2)	234.7 (9.2)	234.7 (9.2)
Open Tailgate to Ground	819.5 (32.3)	883.9 (34.8)	902.5 (35.5)	934.9 (36.8)
Pickup Body Height	511.1 (20.1)	511.1 (20.1)	511.1 (20.1)	511.1 (20.1)





**1500**

CANADIAN SPECIFICATIONS

Approach Angle (degrees)	15.5	19.7	22.3	23.9
Departure Angle (degrees)	22.5	25.5	26.4	27.8
Ramp Breakover Angle (degrees)	16.4	19.8	21.7	23.3
Ground Clearance without Skid Plate	185.8 (7.3)	239.0 (9.4)	268.7 (10.6)	290.0 (11.4)
Ground Clearance with Skid Plate	168.8 (6.6)	221.7 (8.7)	251.7 (9.9)	272.7 (10.7)
Fuel-Tank Capacity	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)

**Crew Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman**

**Tire Size**

**265/70R17**

<b>Suspension Mode</b>	<b>Entry / Exit</b>	<b>Normal Ride Height</b>	<b>Off Road 1</b>	<b>Off Road 2</b>
Wheelbase (nominal)	3798.0 (149.5)	3798.0 (149.5)	3798.0 (149.5)	3798.0 (149.5)
Track, Front	1728.2 (68.0)	1728.2 (68.0)	1728.2 (68.0)	1728.2 (68.0)
Track, Rear	1714.7 (67.5)	1714.7 (67.5)	1714.7 (67.5)	1714.7 (67.5)
Overall Length	6042.6 (237.9)	6042.6 (237.9)	6042.6 (237.9)	6042.6 (237.9)
Overall Width	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)
Overall Height	1897.7 (74.7)	1950.7 (76.8)	1975.2 (77.8)	2001.7 (78.8)
<b>Ground Clearance</b>				
Front Axle	231.6 (9.1)	231.6 (9.1)	231.6 (9.1)	231.6 (9.1)
Rear Axle	217.7 (8.6)	217.7 (8.6)	217.7 (8.6)	217.7 (8.6)
Open Tailgate to Ground	827.9 (32.6)	866.6 (34.1)	885.2 (34.8)	917.6 (36.1)
Pickup Body Height	511.1 (20.1)	511.1 (20.1)	511.1 (20.1)	511.1 (20.1)
Approach Angle (degrees)	15.3	19.7	21.8	22.9
Departure Angle (degrees)	18.6	20.4	21.3	22.7
Ramp Breakover Angle without Skid Plate	15.3	18.7	20.5	22.2
Ramp Breakover Angle with Skid Plate	12.0	15.0	16.6	18.2
Ground Clearance without Skid Plate	170.0 (6.7)	222.7 (8.8)	252.4 (9.9)	273.7 (10.8)
Ground Clearance with Skid Plate	152.3 (6.0)	205.4 (8.1)	235.4 (9.3)	256.4 (10.1)
Fuel-Tank Capacity	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)

**Crew Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman**

**Tire Size**

**275/60R20**

<b>Suspension Mode</b>	<b>Entry / Exit</b>	<b>Normal Ride Height</b>	<b>Off Road 1</b>	<b>Off Road 2</b>
Wheelbase (nominal)	3798.0 (149.5)	3798.0 (149.5)	3798.0 (149.5)	3798.0 (149.5)





# 1500

## CANADIAN SPECIFICATIONS

Track, Front	1742.2 (68.6)	1742.2 (68.6)	1742.2 (68.6)	1742.2 (68.6)
Track, Rear	1727.4 (68.0)	1727.4 (68.0)	1727.4 (68.0)	1727.4 (68.0)
Overall Length	6042.6 (237.9)	6042.6 (237.9)	6042.6 (237.9)	6042.6 (237.9)
Overall Width	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)
Overall Height	1914.5 (75.4)	1967.5 (77.5)	1991.9 (78.4)	2018.5 (79.5)
<b>Ground Clearance</b>				
Front Axle	247.9 (9.8)	247.9 (9.8)	247.9 (9.8)	247.9 (9.8)
Rear Axle	234.7 (9.2)	234.7 (9.2)	234.7 (9.2)	234.7 (9.2)
Open Tailgate to Ground	819.5 (32.3)	883.9 (34.8)	902.5 (35.5)	934.9 (36.8)
Pickup Body Height	511.1 (20.1)	511.1 (20.1)	511.1 (20.1)	511.1 (20.1)
Approach Angle (degrees)	16.6	20.9	22.9	24.0
Departure Angle (degrees)	19.4	21.3	22.1	23.6
Ramp Breakover Angle without Skid Plate	16.4	19.8	21.7	23.3
Ramp Breakover Angle with Skid Plate	13.0	16.0	17.7	19.2
Ground Clearance without Skid Plate	185.8 (7.3)	239.0 (9.4)	268.7 (10.6)	290.0 (11.4)
Ground Clearance with Skid Plate	168.8 (6.6)	221.7 (8.7)	251.7 (9.9)	272.7 (10.7)
Fuel-Tank Capacity	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)	98-litre (Standard) 121-litre (Optional)

### Cargo Box

<b>Nominal Box Size</b>	<b>5 ft 7 in (Crew)</b>	<b>6 ft 4 in (Regular, Quad, or Crew)</b>	<b>8 ft (Regular)</b>
Volume, L (cu. ft.)	1424.3 (50.3)	1628.3 (57.5)	2015.6 (74.7)
Length at Floor, Tailgate Closed	1712.4 (67.4)	1938.5 (76.3)	2496.5 (98.3)
Cargo Width	1686.9 (66.4)	1686.9 (66.4)	1686.9 (66.4)
Distance Between Wheelhouses	1295.4 (51)	1295.4 (51)	1295.4 (51)
Depth	508.6 (20.0)	511.1 (20.1)	513.0 (20.2)
Tailgate Opening Width mm (in.)	1535.3 (60.4)	1535.3 (60.4)	1535.3 (60.4)

### ACCOMMODATIONS

<b>Model</b>	<b>Regular Cab</b>	<b>Quad Cab</b>	<b>Crew Cab</b>
Seating Capacity, F/R	3/0 or 2/0	3/3 or 2/3	3/3 or 2/3
<b>Front</b>			
Head Room	1013.5 (39.9)	1041.4 (41.0)	1041.4 (41.0)
Legroom	1041.4 (41.0)	1041.4 (41.0)	1041.4 (41.0)
Shoulder Room	1676.4 (66.0)	1676.4 (66.0)	1676.4 (66.0)
Hip Room	1598.7 (62.9)	1605.3 (63.2)	1605.3 (63.2)
Seat Travel	230.0 (9.0)	230.0 (9.0)	230.0 (9.0)
Recliner Range (degrees)	85 (38 rwd, 47 fwd)	56 (38 rwd, 18 fwd)	56 (38 rwd, 18 fwd)



**1500**

CANADIAN SPECIFICATIONS

<b>Rear</b>			
Head Room	N/A	1008.4 (39.7)	1013.5 (39.9)
Legroom	N/A	880.9 (34.7)	1023.3 (40.3)
Shoulder Room	N/A	1668.8 (65.7)	1668.8 (65.7)
Hip Room	N/A	1598.3 (62.9)	1605.3 (63.2)
<b>Interior Volume</b>			
Front – L (cu. ft.)	1769.8 (62.5)	1817.9 (64.2)	1817.9 (64.2)
Rear – L (cu. ft.)	N/A	1483.8 (52.4)	1730.2 (61.1)

• • •