

2017 RAM ProMaster™ Specifications



Cargo Van Standard Roof	1500	1500
Wheelbase mm (in)	2997 (118)	3454 (136)
Overall Length mm (in)	4953 (195)	5413 (213)
Vertical Interior Height mm (in)	1651 (65)	1651 (65)
Overall Roof Height mm (in)	2311 (91)	2311 (91)
Cargo Width at Wheel Well mm (in)	1422 (56)	1422 (56)
Overall Body Width with Mirrors mm (in)	2,690 (105.9)	2,690 (105.9)
Load Floor Length mm (in)	2667 (105)	3124 (123)
Cargo Volume L (cu ft)	7334 (259)	8608 (304)
Rear Door Swing (degrees)	260	260
GVWR kg (lb)	3878 (8550)	3878 (8550)
GCWR kg (lb) (gas/diesel)	5216 (11,500) / N/A	5216 (11,500) / 5670 (12,500)
Maximum Payload kg (lb) (gas/diesel)	1810 (3990) / N/A	1760 (3880) / 1642 (3620)

Cargo Van High Roof	1500	2500	2500	3500	3500
Wheelbase mm (in)	3454 (136)	3454 (136)	4039 (159)	4039 (159)	4039 (159) Ext
Overall Length mm (in)	5413 (213)	5413 (213)	5994 (236)	5994 (236)	6350 (250)
Vertical Interior Height mm (in)	1930 (76)	1930 (76)	1930 (76)	1930 (76)	1930 (76)
Overall Roof Height mm (in)	2565 (101)	2565 (101)	2565 (101)	2565 (101)	2565 (101)
Cargo Width at Wheel Well mm (in)	1422 (56)	1422 (56)	1422 (56)	1422 (56)	1422 (56)
Overall Body Width with Mirrors mm (in)	2,690 (105.9)	2,690 (105.9)	2,690 (105.9)	2,690 (105.9)	2,690 (105.9)
Load Floor Length mm (in)	3124 (123)	3124 (123)	3708 (146)	3708 (146)	4064 (160)
Cargo Volume L (cu ft)	9993 (352.9)	9993 (352.9)	11,899 (420.2)	11,899 (420.2)	13,108 (462.9)
Rear Door Swing (degrees)	260	260	260	260	260
GVWR kg (lb)	3878 (8550)	4037 (8900)	4037 (8900)	4241 (9350)	4241 (9350)
GCWR kg (lb) (gas/diesel)	5,216 (11,500) / 5670 (12,500)	5,216 (11,500) / 5670 (12,500)	5,216 (11,500) / 5670 (12,500)	5,216 (11,500) / 5670 (12,500)	5,216 (11,500) / 5670 (12,500)
Maximum Payload kg (lb) (gas/diesel)	1706 (3760) / 1569 (3460)	1869 (4120) / 1737 (3830)	1819 (4010) / 1674 (3690)	2005 (4420) / 1864 (4110)	1969 (4340) / 1823 (4020)

Chassis Cab	3500	3500
Wheelbase	4039 (159)	4039 (159) Ext
Cab to Rear Axle mm (in)	2642 (104)	2642 (104)
Overall Length mm (in)	5944 (230)	6198 (244)
Overall Max Allowable Upfit Length mm (in)	6477 (255)	7391 (291)
Roof Height mm (in)	2311 (91)	2311 (91)
Overall Body Width with Mirrors mm (in)	2,690 (105.9)	2,690 (105.9)
Overhang Rear axle to End of Frame	864 (34)	1219 (48)
GVWR kg (lb)	4241 (9350)	4241 (9350)
GCWR kg (lb) (gas/diesel)	5,216 (11,500) / 5670 (12,500)	5,216 (11,500) / 5670 (12,500)
	2327 (5130) /	2313 (5100) /
Max Payload kg (lb) (gas/diesel)	2218 (4890)	2195 (4840)

Window Van High Roof	2500	3500
Wheelbase mm (in)	159	159
Overall Length mm (in)	5994 (236)	5994 (236)
Vertical Interior Height mm (in)	1930 (76)	1930 (76)
Overall Roof Height mm (in)	2565 (101)	2565 (101)
Cargo Width at Wheel Well mm (in)	1422 (56)	1422 (56)
Overall Body Width with Mirrors mm (in)	2,690 (105.9)	2,690 (105.9)
Load Floor Length mm (in)	3708 (146)	3708 (146)
Cargo Volume L (cu ft)	11,899 (420.2)	11,899 (420.2)
Rear Door Swing (degrees)	260	260
GVWR kg (lb)	4037 (8900)	4037 (8900)
GCWR kg (lb) (gas/diesel)	5,216 (11,500) / 5670 (12,500)	5,216 (11,500) / 5670 (12,500)
Maximum Payload kg (lb) (gas/diesel)	1783 (3930) / 1637 (3610)	1941 (4280) / 1801 (3970)

Cutaway	3500	3500
Wheelbase	4039 (159)	4039 (159) Ext
Cab to Rear Axle mm (in)	2642 (104)	2642 (104)
Overall Length mm (in)	5944 (230)	6198 (244)
Overall Max Allowable Upfit Length mm (in)	6477 (255)	7391 (291)
Roof Height mm (in)	2311 (91)	2311 (91)
Overall Body Width with Mirrors mm (in)	2,690 (105.9)	2,690 (105.9)
Overhang Rear axle to End of Frame	864 (34)	1219 (48)
GVWR kg (lb)	4241 (9350)	4241 (9350)
GCWR kg (lb) (gas/diesel)	5,216 (11,500) / 5670 (12,500)	5,216 (11,500) / 5670 (12,500)
	2359 (5200) /	2336 (5150) /
Max Payload kg (lb) (gas/diesel)	2232 (4920)	2214 (4880)